

Digital Surveillance



SE-100 Series

Embedded DVR With Network Surveillance Software

Unique Features

- Fully developed in Korea
- Embedded Linux system offering maximum stability
- All Channels Real-time Display and Recording (25/30 fps per channel). With All Channel Real-time Playback.
- Support internally up to 4 IDE HDD without additional hardware (with sufficient built-in power and space, no need to upgrade power supply or whatsoever). Each HDD Slot can support more than 300GB (Chipset supports upto 2,000GB per HDD)
- File Backup via IEEE1394, TCP/IP Network and USB
- File Backup to Built-in CD-RW for SE-108C
- MPEG2 compression method for DVD quality image and storage efficient compression
- · Motion / Sensor detection triggered recording
- Triplex Operation and more Recording, Playback, Backup and Remote Access at same time
- Easy operation via Front Panel and Remote Control
- Remote Monitoring and operation via Network Client
 Software
- Pan Tilt Zoom Control

Remote Surveillance Software

- · Remote live viewing
- · Remote network backup and online file list viewing
- · All channel simultaneous viewing
- Remote playback clips backed up via USB, network, IEEE1394 and CD writer.
- Password Controlled
- Playback speed control
- Remote PTZ Control



Rear Side Detail






SecuRex reserves the right to change specifications, modify design and discontinue items without incurring obligation and whilst every effort is made to ensure that description, specifications and other information in this catalogue are correct, no warrant is given in respect thereof and the company shall not be liable for any error therein.

http://www.securexsolution.com/ enquiry@securexsolution.com



Digital Surveillance

System Diagram



Specifications

Model	SE-104S	SE-108S	SE-108C		
Video In	4 Channel (BNC)	8 Channel (BNC)			
Video Out	1 TV Monitor (BNC) / 1 S-Video / 4 Loop Back (BNC)	1 TV Monitor (BNC) (Loop Back by External T-Joint and 750hm On/Off Switch)			
Audio In	2 Channel (RCA) 4 Channel (RCA)				
Audio Out	1 Channel (RCA)				
Display Speed	NTSC 120fps (30fps per channel) PAL 100fps (25fps per channel)				
Display Resolution	NTSC 720 x 480 PAL 720 x 576				
Display Screen	Full, Quad and SPOT	Full, Quad and 8+8			
Recording Resolution	NTSC 360 x 240 (per channel) PAL 360 x 288 (per channel)				
Recording Max. Speed	NTSC 120fps (30fps per channel) PAL 100fps (25fps per channel)		NTSC 240fps (30fps per channel) PAL 200fps (25fps per channel)		
Recording Frame Rate (configurable to)	NTSC (per channel) 30 / 15 / 10 / 6 / 3 / 1 PAL (per channel) 25 / 12.5 / 8.3 / 5 / 2.5 / 1				
Recording Compression	MPEG-2				
Recording Mode	Manual / Event / Schedule				
Recording Compression Rate	3 Steps (Standard / High 1 / High 2)				
Pre-Alarm Recording	Yes				
Playback Search Mode	Time / Event / List Search				
Playback Speed	FF: x2, x4, x8, x16 / Reverse: x1, x2, x4, x8, x16 Slow: x1/2, x1, x1/4, x1/8 / Still and Frame Advance				
Sensor and Alarm	4 Input / 4 Output	8 Input /	8 Output		
Network	via LAN, TCP/IP (Included Client S/W)				
Backup			via USB, IEEE1394, Network or CD Writer		
P/T/Z Control	RS-485				
Operating System	Embedded Linux				
Dimension	430 (W) x 445 (D) x 90 (H) mm				
System Control	Front Key Pad, IR Remote Control				
Power	100 - 220V / 50 - 60Hz / 350W				
Client Software	SE 4 Channel Client Software SE 8 Channel Client Software				

http://www.securexsolution.com/ enquiry@securexsolution.com

SecuRex reserves the right to change specifications, modify design and discontinue items without in-curring obligation and whilst every effort is made to ensure that description, specifications and other information in this catalogue are correct, no warrant is given in respect thereof and the company shall not be liable for any error therein.



Storage Calculation Example (Please use on pro-rata basis)

Frame Rate	Standard Picture Quality		High 1 Pictu	High 1 Picture Quality		High 2 Picture Quality	
(PAL) (Frame/Sec)	240GB	480GB	240GB	480GB	240GB	480GB	
25.00	220hr	440hr	117.9hr	235.8hr	78.5hr	157hr	
12.50	440hr	880hr	235.8hr	471.6hr	157hr	314hr	
8.30	660hr	1,320hr	353.7hr	707.4hr	235.5hr	471hr	
5.00	1,100hr	5,500hr	589.5hr	1,179hr	392.5hr	785hr	
2.50	2,200hr	4,400hr	1,179hr	2,358hr	785hr	1,570hr	
1.00	5,500hr	11,000hr	2,948hr	5,895hr	1,963hr	3,926hr	

Note: This table is basing on SE-104S 4 Channels (retention period is for all 4 channels, i.e. for whole unit). Note: For SE-108S, please divide the retention period by 2.

Note: These are rounded up figures. May varies depends on camera quality and motion level.

Note: For different size of hard disk, please calculate on pro-rata basis. End-user can choose any hard disk capacity available on the market.

Ordering Information

Model	Description
SE-104S	4 Channel Embedded Digital Video Recorder with Remote Surveillance
SE-108S	8 Channel Embedded Digital Video Recorder with Remote Surveillance
SE-108C	8 Channel Embedded Digital Video Recorder with Remote Surveillance and CD Writer Backup

